



76-B4442



CE

ASTM

4

(76-B444X) 6

4

(76-B446X)

76-B446X

6

4



128×80

6

CE



ASTM D1559 ASTM D5581 AASHTO T245 ASTM D6926



	76-B4442 76-B4443 76-B4444	76-B4462 76-B4463 76-B4464
	800W	2000W
(/)	55±5	55±5
	98.5mm	149.4mm
	4536±9g	10.21±0.01kg
	457±3mm	457±2mm
	385×470×1867mm	423×578×1861mm
	150kg	170kg



76-B4442



76-B4442



76-B4000/CB ASTM EN



76-B4442

	4	ASTM D1559, D6926	AASHO
T245		230V 50Hz 1 ph	

76-B4443

	4	ASTM D1559, D6926	AASHO
T245		220V 60Hz 1 ph	

76-B4444

	4	ASTM D1559, D6926	AASHO
T245		110V 60Hz 1 ph	

76-B4462

	6	4	ASTM D5581
		6	4
	230V	50Hz	1 ph

76-B4463

6 4 ASTM D5581
6 4
220V 60Hz 1 ph

76-B4464

6 4 ASTM D5581
6 4
110V 60Hz 1 ph



33-T3712/CB

CBR-Proctor 33-T371X 76-B444X
B443X B446X

76-B4460/1

6 4 76- B446X 4

